Grade 2 Standard Duty Interconnected Lock SERIES



Architectural Submittal Sheet

Typical Applications

- Assisted Living
- Hospitality
- Military Housing
- Multi-family
- Offices
- Retail







Specifications

opoomoutiono	ADA COMPLIANT			
FOR DOORS:	• 1-3/8" and 1-3/4" thick.			
PREPARATION:	ANSI/BHMA A156.115 for 4" and 5-1/2" hole centers, field selectable.			
DUST BOX:	•Included for Latchbolt and Deadbolt.			
LATCHBOLT BACKSET:	• 2-3/8" or 2-3/4" (Default). Specify when ordering			
DEADBOLT BACKSET:	Field adjustable for 2-3/8" and 2-3/4" (Default).			
STRIKE:	"T"-Strike (Default) ASA or Full-Lip optional			
LEVERS:	Boston, Miami, Memphis, Orlando, Philadelphia			
ROSE:	• 2-3/8" Round Rose, 2-15/16" Square Rose			
INSIDE ESCUTCHEON:	• 3-3/4"W x 9-3/4"H (Wrought)			
LATCHBOLT:	• 1/2" Throw			
DEADBOLT:	ADA compliant.			
HANDING:	Non-handed (Except for Memphis Lever)			
KEYS:	• Two (2) per Lock			
KEYWAYS:	SCC Default (Schlage C Compatible). For additional keyways, see Cylinders and Keying section.			
INTERCHANGEABLE CORE:	6-pin or 7-pin Compatible with Best SFIC. Not available in high security.			
CONVENTIONAL KEY IN KNOB/LEVER CYLINDER:	• 6-pin Cylinder keyed to 5-pins			
KEYING:	 Options: MK, CMK, or GMK, Zero Bitted (KO), Keyed Different (KD) or Keyed Alike (KA) Can be keyed into existing master key systems. See Keyways Section. 			
FINISHES:	• 605 (US3) Bright Brass, 613 (US10B) Oil Rubbed Bronze, 622 (US19) Flat Black, 626 (US26D) Satin Chrome (See Note)			
CERTIFICATIONS, LISTINGS, COMPLIANCES:	 ANSI, Grade 2 UL listed for 3 hrs, for single doors up to 4'0" x 8'0" Complies with ADA (Americans with Disabilities Act) and ICC/ANSI 117.1 for Accessible and Usable Buildings 			
WARRANTY:	Two (2) year Limited Warranty			

CL SERIES Grade 2 Standard Duty Interconnected Lock

PDQ Functions

FUNCTION	FUNCTION NUMBER	INSIDE I OUTSIDE	DESCRIPTION	ANSI NUMBER
Entry Single Cylinder Passage Lever	126		 Outside and Inside lever always free Deadbolt projected or retracted by key outside or turnpiece inside When deadbolt is projected, turning inside knob/lever retracts deadbolt and latchbolt simultaneously 	F95
Storeroom Double Cylinder (See note) Passage Lever	115		 Deadlocking latch bolt is operated by key outside or inside lever Key outside projects or retracts dead bolt. Operating inside lever or keys outside retracts dead bolt and deadlocking latch. 	F98
Entry Double Cylinder (See note) Privacy Lever	116		 Outside lever locked by turn button in inside knob/lever Inside lever always free Unlocking of outside lever requires use of key or manual return of inside turn button Deadbolt is activated by key in outside deadlock or turnpiece inside Turning inside lever retracts deadbolt and latchbolt simultaneously 	F97
Privacy with Dead Bolt Indicator No Cylinder Passage Lever	176		 Outside and Inside lever always free Indicator outside Thumbturn inside extends/retracts deadbolt Emergency key outside retracts deadbolt When deadbolt is projected, turning inside lever retracts deadbolt and latchbolt simultaneously 	_

Levers



Philadelphia — PHL



Boston — BSN



Miami — MIA



Memphis — MEM (Specify Handing)



Orlando — ORL





Round Rose



CL SERIES Grade 2 Standard Duty Interconnected Lock



Options

CODE	DESCRIPTION
DB	Dust Box

