



Cylinder

Safety. Security. Peace of Mind.

Typical Applications

- Auxiliary Doors
- Closets
- Commercial/Institutional/Military
- Common Areas
- Equipment Rooms
- Storerooms
- Restrooms
- Privacy Rooms



Standard Thumbturn



Indicator

Small Mortise Body Type Prep

Product Specifications



FOR DOORS:	• 1-3/4"
BACKSET:	• 2-3/4"
CASE:	• Steel — Dichromated for corrosion resistance
FACEPLATE:	• 1-1/4" x 5-5/8"
FRONT:	• 2-1/4" x 1" • Stainless Steel.
STRIKE:	• 1-1/8" x 3-1/2"
DEADBOLT:	• 1" Throw. • Stainless Steel.
THUMBTURN OPTION:	• ADA Compliant.
INDICATOR:	• Vacant/Occupied available.
HAND:	• Non-handed except for function MJ134 Classroom. (See Function Table and How to Order Guide).
KEYS:	• Two (2) per Lock.
KEYWAYS:	• SCC standard (Schlage C Compatible) • Also available in keyways of other manufacturers
INTERCHANGEABLE CORE:	• 6 or 7-pin • SFIC Cores • Large Format IC Cores compatible with Schlage only.
CYLINDER:	• 6 or 7-pin Mortise Cylinder
KEYING:	• Options: MK, CMK or GMK • Zero Bitted (KO), Keyed Different (KD) or Keyed Alike (KA) • Can be keyed into existing master key systems
FINISHES:	• 605 (US3) Bright Brass, 606 (US4) Satin Brass, 612 (US10) Satin Bronze , 613 (US10B) Oil Rubbed Bronze, 629 (US32) Bright Stainless Steel, 630 (US32D) Satin Stainless Steel
WARRANTY:	• 10-Year Limited Warranty

Listings and Certifications

- CERTIFICATIONS, LISTINGS, COMPLIANCES:**
- UL/CUL listed
 - Meets requirements of the Buy American Act.

Finishes



605 (US3)
Bright Brass

606 (US4)
Satin Brass

612 (US10)
Satin Bronze

613 (US10B)
Oil Rubbed Bronze

629 (US32)
Bright Stainless
Steel

630 (US32D)
Satin Stainless Steel