



GRADE 2

Most Valuable Grade 2 on the Market

- 8 Functions, more than most other Grade 2 locks
- Removable through bolts make for easy installation
- Designer lever and finish styles plus a 5-Year Warranty

Product Specifications



| | |
|-----------------------|--|
| FOR DOORS: | • 1-3/8" to 1-3/4" thick • Preset for 1-3/4" door |
| APPLICATION: | • Secure installation using a through bolting process • Fits standard 160 and 161 Door prep with the addition of through bolt holes |
| BACKSET: | • 2-3/4" standard • 2-3/8" optional |
| CHASSIS: | • Heavy-gauge cold rolled steel mechanism • Dichromated for corrosion resistance |
| FRONT: | • 2-1/4" x 1-1/8" or 2-1/4" x 1" • Stainless Steel or Wrought Brass • Beveled 1/8" in 2" |
| STRIKE: | • ASA standard • T-Strike or Full Lip Strike optional • Stainless Steel or Wrought Brass |
| ROSE: | • 3-3/8" DIA Wrought |
| LATCHBOLT: | • 1/2" Throw |
| HAND: | • Non-handed (Except Memphis) |
| TRIM: | • Solid diecast PHL, BSN, MIA, MEM and ORL Levers • Wrought Brass Roses • Concealed Screws |
| KEYING: | • Keyed to your needs , Keys, keyway, SFIC core, cylinder and keying information on pages 36-37. |
| FINISHES: | • 605 (US3), 613 (US10B), 622 Flat Black, 626 (US26D) |
| CASE QUANTITY: | • 6 locksets |
| WARRANTY: | • Five (5) year Limited Warranty |

Listings and Certifications

- CERTIFICATIONS, LISTINGS, COMPLIANCES:**
- UL/CUL 10C listed for 3 hrs, for single doors up to 4'0" x 8'0"
 - Certified to ANSI/BHMA 156.2, Grade 2
 - Complies with ADA (Americans with Disabilities Act) and ICC/ANSI 117.1 for Accessible and Usable Buildings
 - Meets requirements of the Buy American Act.

Levers/Trim



Philadelphia



Boston



Miami



Memphis
(Specify Handing)



Orlando

Finishes



605 (US3)
Bright Brass



613 (US10B)
Oil Rubbed Bronze



622 (US19)
Flat Black



626 (US26D)
Satin Chromium