

GRADE 2



Perfect for Commercial Duty Applications

Features

- UL listed for 3-hour fire door
- Exceeds ANSI/BHMA A156.2 Grade 2
- 10 standard functions
- · Various strike and latch options to accommodate any opening
- · Available in keyways of most major manufacturers
- Tactile abrasive coating option
- Antimicrobial coating option
- One (1) year limited warranty

Typical Applications

- Apartments
- Back-of-House Hotel/Motel
- Heavy-Duty Residential
- Houses of Worship
- Medium Traffic Commercial Applications
- Offices
- Retail Backroom
- Retrofit/Repair/Replacement
- Warehouses

Product Specifications





FOR DOORS:	• 1-3/8" to 1-3/4" thick
BACKSET:	• 2-3/4" standard • 2-3/8", 5" optional
FRONT:	• 2-1/4" x 1-1/8" or 2-1/4" x 1" • Stainless Steel or Wrought Brass
STRIKE:	ASA standard T-Strike or Full Lip Strike Optional
ROSE:	• 3" DIA Wrought
LATCHBOLT:	• 1/2" Throw
HAND:	Non-handed
TRIM:	Stainless Steel or Wrought Brass Knobs and Roses
KEYING:	• Keyed to your needs, Keys, keyway, SFIC core, cylinder and keying information on pages 36-37.
FINISHES:	• 605 (US3), 613 (US10B), 630 (US32D) • Optional Antimicrobial Coating available
WARRANTY:	One (1) Year Limited Warranty

Listings and Certifications

CERTIFICATIONS, LISTINGS, COMPLIANCES:

- Certified to ANSI/BHMA A156.2, Grade 2
- UL/CUL 10C listed for 3 hrs, for single doors up to 4'0" x 8'0"

Finishes

Bright Brass



