**GRADE 1** 



# **Designed for Robust Applications**

#### **Features**

- UL listed for 3-hour fire door
- Exceeds ANSI/BHMA A156.2 Grade 1
- 5 standard functions
- · Various strike and latch options to accommodate any opening
- · Available in keyways of most major manufacturers
- Tactile abrasive coating option
- Antimicrobial coating option
- Five (5) year limited warranty

## **Typical Applications**

- Apartments
- Back-of-House Hotel/Motel
- Commercial Buildings
- Government Buildings
- High Traffic Areas
- Healthcare
- Houses of Worship
- · Military Barracks
- Retail Backroom
- Retrofit/Repair/Replacement

# **Product Specifications**





FOR DOORS:	• 1-3/8" to 2" thick.
DOOR PREP:	• Fits Standard 160 or 161 Door Prep.
BACKSET:	• 2-3/8", 2-3/4", 5".
CASE:	• Steel, Yellow Chromate Plate
FRONT:	• 2-1/4" x 1-1/8" or 2-1/4" x 1" • Stainless Steel or Wrought Bronze.
STRIKE:	• 4-7/8" x 1-1/4" (ASA). "T" or "FL" Strike Optional. • Stainless Steel or Wrought Bronze.
ROSE:	• 3" DIA Wrought.
HAND:	• Non-handed.
TRIM:	Stainless Steel Ball Knob.
KEYING:	• Keyed to your needs, Keys, keyway, SFIC core, cylinder and keying information on pages 36-37.
FINISHES:	• 630 (US32D)
WARRANTY:	• Five (5) Year Limited Warranty

## **Listings and Certifications**

CERTIFICATIONS, LISTINGS, COMPLIANCES:

- Certified to ANSI/BHMA A156.2, Grade 1
- UL/CUL 10C listed for 3 hrs, for single doors up to 4'0" x 8'0"

### **Finishes**



630 (US32D) Satin Stainless Steel

